



150 Brushless Smart ESC Programmable Options

Programmable Items	Parameter Options								
	1	2	3	4	5	6	7	8	9
1. Running Mode	Forward w/ Brake	Forward/Reverse w/ Brake							
2. Drag Brake Force	0%	2%	4%	6%	8%	10%	12%	14%	16%
3. Low-voltage Cutoff	3.2V	3.3V	3.4V	3.5V	3.6V	3.7V			
4. Start Mode/Punch	Level 1	Level 2	Level 3	Level 4	Level 5	Level 6	Level 7	Level 8	Level 9
5. Max Brake Force	25%	37.5%	50%	62.5%	75%	87.5%	100%	(disabled)	
6. Max Reverse Force	25%	50%	75%	100%					
7. Neutral Range	6% (Narrow)	9% (Normal)	12% (Wide)						
8. Timing (Degrees)	0.0	3.75	7.5	11.25	15.0	18.75	22.50	26.25	
9. Motor Rotation	CCW	CW							
10. BEC Voltage	6.0V	7.4V							



150 Brushless Smart ESC Specifications

SPMXSE2150

Cont. Current	150A
Max Burst Current	950A
LiPo Cells	3 – 6S LiPo
BEC Output	6V/ 7.4V Adjustable @ 5A
Size/Weight	2.3" (58mm) x 1.9" (47.5mm) without tabs, 2.3" (59.5mm) with tabs x 1.5" (38.5mm) / 8.4oz (238g)

Waterproof	IP67 rated
Motor Connector	4mm Female Bullet
Battery Input	Dual IC5 (Series) 10AWG / 200mm
Motor Type	Sensorless Brushless
Telemetry	SRXL2 Spektrum Smart Technology

©2023 Horizon Hobby, LLC. Firma and the Firma logo are trademarks of Horizon Hobby, LLC. The Spektrum trademark is used with permission of Bachmann Industries, Inc.



04/23
660810EN Spektrum 150 ESC SPMXSE2150